

# AF SERIES BACKPULSE STYLE SYSTEMS

## AF SERIES BACKPULSE STYLE FILTRATION

### EN-880 SERIES FILTRATION

The design of our backpulse style systems was formulated to improve upon the “usual” disposable design found in replacement media style systems. Unlike all other backpulse filters on the market, the specially designed, permanent membranes in our units are engineered to be backpulsed for cleaning rather than thrown away, and with an efficient design of very short cycle duration.

A specially engineered and fabricated interior design supports the membrane while allowing a backflow cleaning cycle which brings the unit back to full filtration efficiency in minutes. Where backpulse style filtration is chosen, our systems are a cut above the rest with disposal and replacement costs eliminated. EN-880 units are available in single as well as multiple chamber designs in many holding capacities, with partial and full automation also available to suit your needs.

- Maximum flow rate:  
EN-880-1X: Up to 2,700 gph  
EN-880-2X: Up to 5,400 gph  
EN-880-3X: Up to 8,100 gph  
EN-880-4X: Up to 10,800 gph
- Also available in additional multiple chambered designs & holding capacities to provide greatly increased maximum flow rates for larger applications.



*EN-880 - 2X Automatic Backpulse Filtration System*



*EN-880 - 1X Manual Backpulse Filtration System*

20 Summit View Drive, Tamworth, NH 03886 • P.O. Box 10  
Tel: (603) 323-7777 • Fax: (603) 323-7007 • Toll Free: (800) 840-5525  
Internet: <http://www.globalfiltrationsystems.com> • Email: [info@globalfiltrationsystems.com](mailto:info@globalfiltrationsystems.com)

