

Equipment Line Card 2020

345 Mira Loma Ave, Glendale CA 91204 Toll Free at 866 734 9403

Automation (loaders & unloaders)

Slip sheeting
Innerlayer
Outerlayer
Slot pallet
Accumulators
Trolleys



Super small foot print
Heron robot arm
automation options




Batch Ovens

Convection
Single & dual chamber
Vacuum
Nitrogen
High Temperature
Clean-Room
Various rack systems



Brushing & Cleaning

Pumice &
Aluminumoxide
brushing
Deburr Machines
Nylon brush cleaning
Post HASL cleaning
Small parts washer



Hole Checking

Post deburr
conveyorized



Drill quality analyzer
Hole positions
Hole quality
Routed board features
CMM function
Lines & spaces



Conveyor Ovens

UV Single & double
sided, Cool
IR conveyor
Screen drying oven
Rack conveyor
Hang conveyor



Cross Sectioning

S-OSR: Coupon router with precision saw
 SPA: Polishing system
 OSR: Coupon router
 No pins needed
 Simple method for laser vias



Drilling & Routing

To 7 stations
 Sieb & Meyer
 Pressure foot
 Depth control
 Broken tool detection



Dry Film Lamination & Peeling

25 um to 6mm possible
 Pre-heater unit
 Post Laminator unit for difficult jobs



Mylar Peeler

Electrical Test

GridTesters

Double and or Quad Density

Flying probe testers

Double tester with robotic loading & unloading



Exposure

UV DMD Direct Image
 ED1500 & 700
 Very large format available
 R2R
 365-450nm lamp spectrum



UV phototool exposure machines

Hot Air Leveling

HASL machines
 Fluxers
 Cooling units
 Air Cleaners
 & more



Ink Jet Printing



Nomenclature

Ink recycling
 Serialization
 UV pinning

Lamination



Electric
 Hot oil
 800F High temperature
 Automation
 Lay-up and de-booking
 tables
 Depinning unit

Lamination Area Tools




Tooling hole drilling
 Spot facer



Innerlayer & prepreg
 dispensing

Post Lamination
 Marking

Bevel and Shear
 Equipment



Lamination Registration



Inductive bonding
 No pin tooling during
 lamination
 Compatible with
 Multiline and two pin
 lay-up
 Quadrant bonding
 system for rigid-flex

Measurement



Automatic & manual
 panel thickness

Line width gauge
 Artwork measurement

Drill & routing quality
 analyzer
 Routed board
 measurement
 Coordinate
 measurement system
 (CMM)

Blind via inspection
 equipment



Photo-plotter

From 20.5" x 26"
to 34" x 56"
Up to 50,000 DPI
0.32mil line width
possible



Plasma Desmear

Vertical gas flow
Excellent uniformity



R2R



Plating

Vertical Plating lines

Excellent uniformity
Compact design
Linear drive system
Cableless data transfer



Screen Printing

From hand to full
automated

NEW

Vertical printer
No ink dripping
Less mask in holes
High productivity



Spray Coating

Single & double sided
Pump delivery system
Parts cleaner
Gap reduction
Double spray gun



Via Fill

Vertical
Horizontal
With & without vacuum
Silver paste processing
Table top system
Manual & automatic
scavenger
Head Cleaning unit
Paste recycle unit



**Via Fill
Sanding
(Planarization)**

Conveyorized sanding
10 brushes or single
brush version

Dry orbital manual
sanding or wet orbital
manual sanding



Via Plugging

Selective with stencil
for via plug with and
without vacuum.

Stand alone vacuum
ovens available



V-Scoring

Pin or Camera
Registration
Various levels of
automation
Metal Laminate
Scoring Equipment



Wet Process

Oxide
Pre-clean
Developer
Stripper
DES & SES
Sn Strip
Other

